

USB 3.1/2 is port covered - some long paper

Xerox® VersaLink® B625 MFP

Configuration Report

Printed at Nov 15, 2024 05:14 PM



Common User Data

Machine Name: Xerox VersaLink B625 MFP (AC:17:78)
 IP Address: 10.61.16.75
 Machine Serial Number: 5321605321
 Fax Line1:
 Machine URL: https://10.61.16.75
 Machine Activation Date: Nov 14, 2024 19:06:54
 Total Impressions: 1920

Machine Profile

Xerox Asset Tag:
 Customer Asset Tag:
 Service Phone Number:
 Customer Support Number:
 Supplies Phone Number:
 System Administrator: System Administrator name not set
 Machine Location: machine location not set

Managed By

Primary MB Server:

Machine Hardware

Fax Card: Not Present
 Fax Memory Size: 0 MB
 Foreign Interface Card: not present
 Device RAM Size: 3904 MB
 Device Storage Size: used=2838MB/total=13925MB (eMMC)
 EPC Memory Size: 187 MB
 Productivity Kit: Not Installed
 Finisher Type: Simple Catch Tray
 Finisher Punch: None
 Finisher Folder: not present
 Multi-feed Detection Kit: Not Installed

General Setup

Remote Services: Enabled
 Remote Software Download: Enabled
 Remote Services Trans. Time: 19:10
 Xerox Workplace Cloud: Disabled
 E-mail Alerts: Disabled
 Service Plan: Metered
 Geographic Region: unknown
 GMT Offset: +05:30
 Cloning Installation: Allowed (Encrypted Files Only)
 File Sharing: Enabled
 JBIG2: Lossless

Energy Saver

Deep Sleep: Enabled
 Energy Saver Mode: Job Activated

Smart Proximity Sensor

Wake on Arrival: Not Available
 Sleep on Departure:

Software Versions

Device Software: 122.025.004.31210
 Patch Version: None
 Network Controller: 122.025.31210
 UI Panel Firmware: 6.1
 Marking Engine: 230.314
 Document Feeder: 230.314
 Finisher: 000.000.000
 Fax: 000.000.000
 Scanner: 230.314

Machine Upgrades:

Last Successful Upgrade: November 11, 2024 21:07:53

Media Trays

Tray 1: Plain, White and A4 (210 x 297 mm)
 Tray 2: Plain, White and A4 (210 x 297 mm)
 Tray 3: Plain, White and A4 (210 x 297 mm)
 Tray 4: Plain, White and Letter (8.5 x 11")
 Bypass Tray: Cardstock, White and Letter (8.5 x 11")

Installed Options

PS: Installed

Connectivity

Mobile Workflows

AirPrint Printing: Enabled
 Mopria Printing Discovery: Enabled
 AirPrint / Mopria Scanning Authentication: Enabled
 Disabled

Physical Connections

USB Settings

USB Type A Ports: All Enabled
 USB Type B Port: Enabled
 Wired: Enabled
 Ethernet MAC Address: 78:8c:77:ac:17:78
 Ethernet Speed/Duplex Setting: auto
 Disabled

Wireless:

Wireless MAC Address:
 Network Name (SSID):
 BSSID:
 Security Mode:
 Encryption Algorithm:
 Status: Enabled
 Wi-Fi Direct: Not Installed

Wireless Hardware:

Wi-Fi Protected Setup (WPS) Name:
 Access Point (SSID):
 Show Password on Device Touch Screen:

NFC:

iBeacon (Bluetooth®) for AirPrint Di... Enabled
 iBeacon Hardware: Enabled
 Bluetooth Device Address: Not Installed
 iBeacon IP Address:

Protocols

TCP/IPV4:

IP Address: 10.61.16.75
 Subnet Mask: 255.255.255.0
 Router/Gateway: 10.61.16.1
 Automatic Addressing: DHCP
 DHCP Server: 10.61.13.223
 DHCP Lease Expiration: Fri Nov 22 16:12:49 2024
 BOOTP Broadcast: Disabled
 Self Assigned Address State: Enabled
 Self Assigned Address:

TCP/IPV6:

Link Local Address: Enabled
 fe80::7a8c:77ff:feac:1778
 Use Router Supplied Prefix: Enabled
 Stateless Global Address 1: Enabled
 Stateless Global Address 2: id00:0:2:116:7a8c:77ff:feac:1778
 Manual Address: :
 DHCP Addressing: Use DHCP as directed by a router
 DHCP Address: fe80::8afc:5dff:fe75:e282
 Default Gateway:
 DUID (DHCP Unique Identifier):

DNS Settings:

Requested Host Name: XRX788C77AC1778
 Verified Host Name:
 Requested Domain Name:
 Verified Domain Name:
 Multicast DNS: Enabled
 Release DHCP Leases and DNS Registrat... Disabled
 Primary DNS Server: 10.61.7.15
 Prefer IPv6 DNS over IPv4: Enabled

Bonjour:

Bonjour Printer Name: Xerox VersaLink B625 MFP (AC:17:78)

HTTP:

Force Traffic over Secure Connection (H... Enabled
 IPP: Yes
 Enabled

SNMP


SNMP v1/v2: Enabled
 SNMP v3: Disabled
 LPR/LPD: Enabled
 Raw IP Printing: Enabled

LDAP

LDAP Server 1 Primary LDAP Address: 0.0.0.0:389
 LDAP Server 1 Search Directory Root:
 LDAP Server 1 Secure Connection (LDA... Disabled
 LDAP Server 1 Validate Server Certificate... Disabled

SMTP

SMTP Server: 10.61.9.241.25
 Connect Encryption (TLS): No Encryption
 Validate Server Certificate (TLS):



Protocols (cont.)

POP3
 POP3 Server: 0.0.0.0:110
 POP3 Secure Connection (TLS): Disabled
 E-mail Address:
 NTP: Disabled
 FTP Client: Enabled
 FTP Client Mode: Passive
 Web Services on Device: Enabled

Apps

Printing

Banner Sheet: Enabled
 Error Sheets: Enabled
 Paper Substitution: Enabled
 Tray Priority: 1,2,3,4,5
 Archival Marking Mode: Off
 PostScript: Installed
 Level: 3
 Version: 3021.101
 PCL
 Version: 6
 Font Name: Courier
 Custom Color Tables: Enabled
 Label: Not Installed
 Fax: Not Present
 Fax Line 1:
 Fax Line 2:

Server Fax:

Repository Protocol: Enabled
 Repository Server: FTP
 Repository Document Path: 0.0.0.0

Workflow Scanning:

Enabled

Email:

Enabled

Scan to Mailbox:

Enabled/Displayed

Storage Capacity (MB): 672 MB

Storage Used (MB): 109 MB

Cleanup of Public Folders: Enabled

Cleanup of Created Folders: Enabled

Cleanup Time: Daily

Scan to Home:

Disabled

Scan To:

Enabled

Cloud Services: Enabled

Print From:

Enabled

Saved Jobs for Reprint: Enabled/Displayed

Print From USB: Disabled

Print From MailBox: Disabled

Cloud Services: Enabled

Accounting

Accounting Mode: None
 Network Accounting: Disabled

Security

Authentication Configuration

Machine UI Authentication: Remotely on the Network
 Home: Unlocked
 Jobs: Unlocked
 Device: Unlocked
 Device Website Authentication: Remotely on the Network
 Authorization: Locally on the Device
 Retrieve E-mail from LDAP: Enabled

Authentication Server:

SMB

Xerox Secure Access:

Disabled

Audit Log:

Enabled

IP Sec:

Disabled

IP Filtering:

Disabled

Security Certificates

Machine Certificate: Signed

Root Certificates Installed: 71

802.1x:

Disabled

Job Data Removal:

Scheduled: Disabled

FIPS 140-3:

Disabled

TLS:

TLS 1.1 and TLS 1.2

TLS Hash:

SHA-1, SHA-256 and above

Trellix Embedded Control:

Disabled